Product Datasheet

A2020 Circularly Polarised Antenna

Times-7 is a high-tech company specialising in the design and manufacture of fixed RAIN RFID antennas.

Our journey began in 2006, when Times-7 was founded. Since then, we have developed the largest portfolio of fixed RAIN RFID reader antennas, known for their SlimLine™ design, quality, and performance.

Our antennas cover:

- A wide variety of RF characteristics
- A range of sizes
- Leading temperature performance
- Range of IP ratings

If your deployment requires a specialisation that is not met by our standard portfolio, we can design and manufacture customised antennas to meet your needs.


We are based in Lower Hutt, New Zealand, with a global reach as we export our products through our extensive authorised partner network.

In addition to our reliable, high quality RAIN RFID antennas, customers appreciate Times-7's customer service and in-depth technical support.

We are responsive in supporting a large global customer base and ensuring the success of our customers' RFID implementations.

Patent information:
www.times-7.com/patents

Times-7 Research Ltd
10 Te Puni Street
Lower Hutt 5012
New Zealand



A2020 rear view

The A2020 Circularly Polarised Antenna is designed for indoor environments where space is limited but RF performance cannot be compromised.

With a compact 129 × 129 mm footprint and slim 14.2 mm profile, the A2020 integrates seamlessly into space-constrained installations. Its wide, symmetrical 100° beamwidth and 5 dBiC gain provide a controlled read zone and dependable RF performance. Weighing just 0.154 kg, with 100 × 100 mm VESA mounting and a rear SMA connection, it can be discreetly integrated into shelving, cabinets, workstations and other tight spaces.

Offering similar RF performance and footprint to the popular A5020CP, the A2020 is purpose-built for high-volume indoor deployments. It is IP54 rated, operates from -20°C to +55°C (-4°F to +131°F), and is compatible with any standard RAIN RFID reader.

ORDERING INFORMATION

Note:
Please quote part number, frequency range, and cable type.

Antenna	Frequency Range	Part Number
A2020	ETSI 865-868 MHz	75663
A2020	FCC 902-928 MHz	75664
A2020 (Bulk Pack- 50 units)	ETSI 865-868 MHz	75785
A2020 (Bulk Pack- 50 units)	FCC 902-928 MHz	75786

Cable Accessories	Cable Type	Part number
Cable 2m, SMA to RP-TNC	T7 195 / T7 240 / T7 400	71436 / 71782 / 72042
Cable 4m, SMA to RP-TNC	T7 240 / T7 400	71784 / 72043
Cable 6m, SMA to RP-TNC	T7 240 / T7 400	71904 / 72044
Cable 8m, SMA to RP-TNC	T7 240 / T7 400	71788 / 72045

©2026 Times-7 Research Ltd. All rights reserved. Specifications are subject to change without notice.

Product Datasheet

A2020 Circularly Polarised Antenna

PHYSICAL / ENVIRONMENTAL SPECIFICATIONS

Antenna Dimensions: (L x W x D)	129 x 129 x 14.2 mm (21 mm incl. connector) 5.08" x 5.08" x 0.56" (0.83" incl. connector)
Antenna Weight:	Net: 0.2 kg / 0.3 lbs. Gross (Box of 1):0.2 kg / 0.4 lbs.
Boxed Dimensions (Bulk pack-50 units): (L x W x D)	780 x 205 x 205 mm 30.7" x 8.07" x 8.07"
Box Weight (Bulk pack-50 units):	18.9 kg / 41.7 lbs.
Radome Material:	Flame-retardant and UV-resistant ABS
Environmental Rating:	IP54
Operating and Storage Temperature:	-20°C to +55°C /-4°F to +131°F
Mounting:	Accommodates 100 x 100 mm VESA M6 or 1/4" fasteners
Connector Type:	Rear SMA Jack
RoHs & REACH Compliant	Yes

ELECTRICAL SPECIFICATIONS


Frequency Range:	865-868 MHz (ETSI) / 902-928 MHz (FCC)
Polarisation:	Right hand circularly polarised
Far-Field Gain:	5 dBiC typical
***Far-Field 3dB Beamwidth:**	100° in both planes
VSWR:	1.5 typical
Front-To-Back Ratio:	-10 dB
Axial Ratio:	2 dB typical
Nominal Impedance:	50 Ω
Maximum Input Power:	3 W

©2026 Times-7 Research Ltd. All rights reserved. Specifications are subject to change without notice.


Product Datasheet

A2020 Circularly Polarised Antenna


AZIMUTH PLANES



RADIATING PATTERNS



A2020 XZ Plane



A2020 YZ Plane


APPLICATIONS

Component storage and Kanban monitoring



Monitors tagged components and bin status to support timely replenishment and reduce the risk of parts shortages. The A2020's wide 100° beamwidth enables multiple adjacent bins to be monitored from a single mounting point.

Distribution, sorting and shipment verification



Tracks tagged cartons and pallets through key distribution and shipping stages, providing visibility as goods move through the supply chain. The A2020's mid-gain performance is well suited to readpoints at sorting areas, transition zones and other key chokepoints.

Point-of-sale and collection counters



Verifies tagged items at checkout or collection points without the need to scan each item individually. The A2020's controlled read zone helps isolate items at the counter readpoint while minimising unwanted reads from surrounding stock.

For more antenna recommendations by applications, **visit https://www.times-7.com/applications**

sales@times-7.com | +64 4 974 6566 | www.times-7.com

©2026 Times-7 Research Ltd. All rights reserved. Specifications are subject to change without notice.


Product Datasheet

A2020 Circularly Polarised Antenna

MOUNTING AND INSTALLATION INSTRUCTIONS

The A2020 supports both flush mounting and VESA 100 mounting, providing flexibility across a range of installations.

- **VESA 100 mounting:** The recessed corner mounting holes are compatible with standard 100 × 100 mm VESA-spaced mounting brackets.
- **Flush mounting:** The A2020's slim profile and recessed corner holes allow it to be mounted directly to a suitable surface using screws or bolts.
- **Connector clearance:** Allow sufficient clearance behind the antenna for the rear SMA connector and cable attachment. The installation should provide enough space for easy onsite connection and finger tightening.
- **Connector tightening:** Tighten the SMA connector finger-tight only. Do not use tools, as excessive force may damage the connector.
- **Cable handling:** Avoid excessive pulling or strain on the cable and maintain an appropriate bend radius to prevent damage and ensure reliable operation.



A2020 Antenna
with VESA 100 bracket


The technical data contained in this publication is not a guarantee for which Times-7 Research Ltd assumes legal accountability. It is indicative of typical performance, and if required should be relied on for specific applications only after due verification.

All technical data, specifications and other information contained herein are deemed to be the proprietary intellectual property of Times-7 Research Ltd. No reproduction, copy or use thereof may be made without the express written consent of Times-7 Research Ltd.

Times-7, and the stylized T-7 Antennas logo are trademarks or registered trademarks of Times-7 Research Ltd. All other trademarks are the property of their respective owners.

©2026 Times-7 Research Ltd. All rights reserved. Specifications are subject to change without notice.

MECHANICAL DRAWING FOR A2020 CIRCULARLY POLARISED FLUSH ANTENNA



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TIMES-7 LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TIMES-7 IS PROHIBITED.	DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED TOLERANCES: NO DECIMAL PLACES ± 1 ONE PLACE DECIMAL ± 0.5		DESCRIPTION A2020 CIRCULARLY POLARISED ANTENNA
DRAWN BY: M. PRICE		DATE: 10-4-26	
APPROVED BY: P. WILCOCK		DATE: 4-5-26	SIZE A3 PART NO. 75663 ETSI, 75664 FCC REV A DO NOT SCALE DRAWING Sheet 1of 2

©2026 Times-7 Research Ltd. All rights reserved. Specifications are subject to change without notice.